


# 2/3" STANDARD

LM6JC LM8JC LM12JC LM16JC LM25JC LM35JC LM50JC LM75JC LM100JC

# JC Series


- ▶ High resolution ▶ Low distortion ▶ Excellent cost performance
- ▶ Compact, lightweight and durable ▶ Excellent corner brightness

**LM6JC**



2/3" 1/1.8" 1/2" 6mm **FIXED** **C-mt** **METAL**  
Fixed Focal Megapixel C-mount

**LM8JC**



2/3" 1/1.8" 1/2" 8mm **FIXED** **C-mt** **METAL**  
Fixed Focal Megapixel C-mount

**LM12JC**



2/3" 1/1.8" 1/2" 12mm **FIXED** **C-mt** **METAL**  
Fixed Focal Megapixel C-mount

**LM16JC**



2/3" 1/1.8" 1/2" 16mm **FIXED** **C-mt** **METAL**  
Fixed Focal C-mount Metal Body

**LM25JC**



2/3" 1/1.8" 1/2" 25mm **FIXED** **C-mt** **METAL**  
Fixed Focal C-mount Metal Body

**LM35JC**



2/3" 1/1.8" 1/2" 35mm **FIXED** **C-mt** **METAL**  
Fixed Focal C-mount Metal Body

Model	LM6JC	LM8JC	LM12JC	LM16JC	LM25JC	LM35JC	
Focal Length(mm)	6	8	12	16	25	35	
Image Size(mm)	8.8×6.6(Φ11)	8.8×6.6(Φ11)	8.8×6.6(Φ11)	8.8×6.6(Φ11)	8.8×6.6(Φ11)	8.8×6.6(Φ11)	
Iris Range(F-stop)	F1.4-F16	F1.4-F16	F1.4-F16	F1.4-F16	F1.4-F16	F1.4-F16	
Focusing Range(m)	0.1-∞	0.1-∞	0.1-∞	0.2-∞	0.2-∞	0.3-∞	
Control	Iris Focus	Manual Manual	Manual Manual	Manual Manual	Manual Manual	Manual Manual	
Shooting Range at M.O.D.(mm)	190.6(H)×130.3(V)	136.0(H)×96.1(V)	81.1(H)×59.4(V)	111.8(H)×82.6(V)	72.1(H)×53.7(V)	76.0(H)×56.9(V)	
Angle of View	2/3 Inch 1/1.8 Inch (Degrees)	81.9×61.2 66.9×50.1 59.4×44.5	64.2×47.7 52.4×39.1 46.2×34.6	42.5×31.7 34.6×25.9 30.7×23.0	30.5×22.8 23.8×18.7 22.2×16.6	21.0×15.7 17.2×12.9 15.3×11.4	14.4×10.8 11.8×8.8 10.5×7.9
Resolution(Center, Corner)	100lp/mm, 60lp/mm	100lp/mm, 60lp/mm	100lp/mm, 60lp/mm	100lp/mm, 60lp/mm	100lp/mm, 60lp/mm	100lp/mm, 60lp/mm	
TV Distortion(%)	-10.7	-6.2	-2.5	-1.5	-0.6	-0.2	
Back Focus in Air(mm)	11.3	11.3	11.1	12.1	10.3	14.9	
Mount	C-mount	C-mount	C-mount	C-mount	C-mount	C-mount	
Filter Thread(mm)	-	M27×P0.5	M27×P0.5	M27×P0.5	M27×P0.5	M30.5×P0.5	
Size(mm)	Φ30×32.8	Φ30×30	Φ30×31.5	Φ30×28	Φ30×28	Φ32×36.5	
Weight(g)	65	60	63	55	55	85	
Temperature Range	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	

† Images may differ from the actual product.

# 2/3" & 1/1.8" STANDARD

LM6JC LM8JC LM12JC LM16JC LM25JC LM35JC LM50JC LM75JC LM100JC

## LM50JC



2/3" 1/1.8" 1/2" 50mm **FIXED** **C-mt** **METAL**  
Fixed Focal C-mount Metal Body

## LM75JC



2/3" 1/1.8" 1/2" 75mm **FIXED** **C-mt** **METAL**  
Fixed Focal C-mount Metal Body

## LM100JC



2/3" 1/1.8" 1/2" 100mm **FIXED** **C-mt** **METAL**  
Fixed Focal C-mount Metal Body

Model	LM50JC	LM75JC	LM100JC
Focal Length(mm)	50	75	100
Image Size(mm)	8.8×6.6(Φ11)	8.8×6.6(Φ11)	8.8×6.6(Φ11)
Iris Range(F-stop)	F2.0-F22	F2.5-F22	F2.8-F32
Focusing Range(m)	0.5-∞	1.2-∞	2.0-∞
Control	Iris Focus	Manual Manual	Manual Manual
Shooting Range at M.O.D.(mm)	85.0(H)×63.6(V)	132.6(H)×99.6(V)	168.8(H)×126.6(V)
Angle of View	2/3 Inch 1/1.8 Inch (Degrees)	10.1×7.6 8.2×6.2 7.3×5.5	6.7×5.0 5.5×4.1 4.9×3.7
Resolution(Center, Corner)	100lp/mm, 60lp/mm	100lp/mm, 60lp/mm	100lp/mm, 60lp/mm
TV Distortion(%)	-0.1	-0.1	-0.05
Back Focus in Air(mm)	17.2	18.0	19.0
Mount	C-mount	C-mount	C-mount
Filter Thread(mm)	M30.5×P0.5	M34×P0.5	M40.5×P0.5
Size(mm)	Φ32×39.5	Φ36×51	Φ42×70
Weight(g)	90	100	140
Temperature Range	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C

### Diagram of M.O.D. / Magnification Using A Close Up Ring

Model	LM6JC	LM8JC	LM12JC	LM16JC	LM25JC
(Non)M.O.D./Magnification	100mm/0.06x	100mm/0.07x	100mm/0.12x	200mm/0.08x	200mm/0.12x
(1mm Ring)M.O.D./Magnification	-	-	50mm/0.19x	110mm/0.14x	136mm/0.15x
(5mm Ring)M.O.D./Magnification	-	-	-	-	46mm/0.31x
(10mm Ring)M.O.D./Magnification	-	-	-	-	-
(20mm Ring)M.O.D./Magnification	-	-	-	-	-

Model	LM35JC	LM50JC	LM75JC	LM100JC
(Non)M.O.D./Magnification	300mm/0.12x	500mm/0.10x	1200mm/0.07x	2000mm/0.05x
(1mm Ring)M.O.D./Magnification	240mm/0.14x	422mm/0.12x	1010mm/0.08x	1700mm/0.06x
(5mm Ring)M.O.D./Magnification	132mm/0.26x	264mm/0.20x	630mm/0.13x	1060mm/0.10x
(10mm Ring)M.O.D./Magnification	84mm/0.40x	183mm/0.30x	440mm/0.20x	740mm/0.15x
(20mm Ring)M.O.D./Magnification	-	117mm/0.50x	285mm/0.34x	480mm/0.25x

# 1/1.8" STANDARD

# NCL Series

- ▶ 4 wide angle lenses ▶ Locking screws ▶ Metal body

## LM4NCL



1/1.8" 1/2" 1/3" 3.5mm **FIXED** **C-mt** **METAL**  
Fixed Focal Megapixel C-mount

## LM5NCL



1/1.8" 1/2" 1/3" 4.5mm **FIXED** **C-mt** **METAL**  
Fixed Focal Megapixel C-mount

## LM6NCL



1/1.8" 1/2" 1/3" 6mm **FIXED** **C-mt** **METAL**  
Fixed Focal Megapixel C-mount

## LM12NCL



1/1.8" 1/2" 1/3" 12mm **FIXED** **C-mt** **METAL**  
Fixed Focal Megapixel C-mount

Model	LM4NCL	LM5NCL	LM6NCL	LM12NCL
Focal Length(mm)	3.5	4.5	6	12
Image Size(mm)	7.2×5.4(Φ9)	7.2×5.4(Φ9)	7.2×5.4(Φ9)	7.2×5.4(Φ9)
Iris Range(F-stop)	F1.4-F16	F1.4-F16	F1.4-F16	F1.4-F16
Focusing Range(m)	0.2-∞	0.2-∞	0.2-∞	0.3-∞
Control	Iris Focus	Manual Manual	Manual Manual	Manual Manual
Shooting Range at M.O.D.(mm)	679.9(H)×389.3(V)	405.3(H)×273.8(V)	255.8(H)×188.7(V)	189.9(H)×140.0(V)
Angle of View	1/1.8 inch 1/2 inch (Degrees)	117.7×86.7 103.6×76.7 76.7×57.7	88.8×66.9 79.0×59.4 59.4×45.1	62.7×48.4 57.3×44.0 44.0×33.7
Resolution(Center, Corner)	100lp/mm, 60lp/mm	100lp/mm, 60lp/mm	100lp/mm, 60lp/mm	100lp/mm, 60lp/mm
TV Distortion(%)	-28.0	-17.5	-1.0	-0.8
Back Focus in Air(mm)	8.9	10.0	9.5	11.1
Mount	C-mount	C-mount	C-mount	C-mount
Filter Thread(mm)	-	-	M25.5×P0.5	M25.5×P0.5
Size(mm)	Φ31×30.5	Φ31×29.5	Φ31×34	Φ31×29.5
Weight(g)	60	55	60	55
Temperature Range	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C	-10°C~+50°C

Contact:

[imageoptics.co.uk](http://imageoptics.co.uk)

Tel +44(0)118 979 3727

### Diagram of M.O.D. / Magnification Using A Close Up Ring

Model	LM4NCL	LM5NCL	LM6NCL	LM12NCL
(Non)M.O.D./Magnification	200mm/0.018x	200mm/0.02x	200mm/0.03x	300mm/0.08x
(1mm Ring)M.O.D./Magnification	-	-	22mm/0.19x	93mm/0.12x
(5mm Ring)M.O.D./Magnification	-	-	-	22mm/0.45x

† Images may differ from the actual product.